

Investigation Report - (Investigation UID - IR/TTK/SII/25/00027)

Investigation Information

Investigation UID	IR/TTK/SII/25/00027	I INVASTINATION L.ATANOTV	Injury - Hospitalization Investigation Report
Investigation Status	Final Report Released	Created On	10-Oct-2025 10:36:30 AM
Approver Names	Sayan Mondal, Lalit Aditya Kola, Mounika Laisetti		

Incident Information

Incident UID	IMF/TTK/COI/IAP/25/00040	Incident Catedory	Injury-same as prod- don't delete
Site Name	Coimbatore	Department Name	Maintenance
Incident Status	FinalReportReleased	Created On	10-Oct-2025 10:06:14 AM
Reported By	Lalit Aditya Kola		

Sections

Immediate Action Taken: (Reference from FIR)	Immediately turned off power to the heat-sealing machine. Provided first aid at OHC – burn ointment applied, wound cooled with running water, and bandaged. Area cordoned off to prevent others from touching the hot machine surface. Warning signage "HOT SURFACE – DO NOT TOUCH" displayed near the equipment. Operator briefed on safe shutdown and lockout
	procedure.

Occurence:- Repetitive/New

If Repetitive,Last date of incident: NA	Plant: Packaging Area	Department: Dept 2	Line : Heat-Sealing Machine Line 3
---	-----------------------	--------------------	---

Root Cause Analysis

S.No	Why	Root Cause:: Inadequate identification of residual heat hazards.
1	I WIIV UIU LIIE ODELALOI SUSLAIII A I	Missing visual indicators or warnings on hot equipment. Lack of training on cooldown safety and machine isolation.

Preventive Action

S.No	Action	Responsibility	Target date for completion
1	Install temperature indicator / warning label on sealing plate	EHS Head	2025-10-13
2	Include "Cool Down Before Touch" in LOTO (Lockout- Tagout) checklist	Site EHS	2025-10-15

Reviews and Learning

Documents Revised Based on CAPA: Preventive Maintenance SOP (Rev. 2.3): Updated with "Residual Heat Verification Step". Lockout-Tagout (LOTO) Checklist: Added "Cool-down Confirmation" section.

Machine Safety Signage Register: New signage entries added for heat-sealing units.

Lessons Learned: Even after shutdown, latent hazards such as heat can cause injury — ensure "zero energy state" before physical contact.

Always verify OEM recommendations and adapt them to site safety standards.

Ensure visual warnings and indicators (like temperature gauges) are installed on all equipment with heat or energy retention. Post-incident communication helps build awareness and prevents recurrence.