Doc No: MHCPL-EHS-PTW-09



Permit To Work Report - Lifting Work (Permit UID - APA/APS/MYHINT/LW/0001)

Type of permit	Lifting Work						
Name of project/ site	Aparna New Site						
Contractor company	Mahindra Pvt						
Name of client/ contractor	Raj Kumar Pativada						
Work location							
Users involved							
Other users involved							
Scope of work							
Work permit start date	11/22/2024 12:00:00 AM						
Work permit start time	11/22/2024 11:30:00 PM						
Work permit close date	11/23/2024 12:00:00 AM						
Work permit close time	11/23/2024 12:35:00 AM						
No. of workers	10						
Tools/ equipments to be used							
Description of work	Lifting work (Testing)						
Reference permit no.							
Location	NA						
Hazards							
	Crane Collapse	Falling Objects	Load Fa		Sling Failure		
	Overloading 🗸	High Wind	Bad Wea	ather 🗀	Hit by Load □		
	Other Hazards :						
	Attachments			Image - 1			

Precautions								
taken	Swing Area Barricading 🔽	Follow SWL of Crane / Sling	Adequate Illuminiation 🔽					
	HIRA Undertaken ▼	Good Housekeeping ▼	Good Sling Angle ▼					
	Proper Supervision ✓	Safe Access / Egress ▽	Awareness on expected emergencies ? ✓					
	Other Precautions :		'					
	Attachments File - 1							
Toolbox talks	{ToolboxTalks}							
PPEs	Safety Shoes 	Hand Gloves ☑	Goggles 					
	Other PPE's :							
Safety considerations	Cranes/Hydra crane should not be used for side pulls. Only freely suspended load may be side pulled.							
	Is Certified rigger medically fit & sufficiently trained?							
	Make sure operator must avoid carrying loads over people.							
	Make sure hook have safety latch. The load is well balanced. Avoid tip loading, and loading on hook latch.							
	Special permission to be obtained from site in charge after considering following guidelines for travelling with suspended load.(Try to avoid By travelling with suspended load)							
	Use tested lifting tool-tackles of appropriate capacity.(sling / synthetic belt / D-shackle / tailing hook etc.)							
	Ensure that the deployed operator is well trained, licensed, experienced, and competent to operate the particular Hydra crane to which they are assigned on the particular job involved.							
	Do not use slings, eye bolts, shackles, or hooks that have been cut, welded, or brazed.							
	Initially lift the load only a few inches to test the rigging and balance Loads should be well secured.							
	While any employee is touching the load or hook, there shall be no Hoisting, lowering, or traveling.							
	when the load or hook approaches near or over persons, the warning signal shall be sounded.							
	Make sure to complete the entire lifting operations on during the day light only. If at all to be carried during night hours ensure to provide sufficient lighting.							
	Make sure that no worker or any person is allowed to stay at lifting area. Avoid unauthorized entry. (Like Cars, Two wheelers, & pedestrians)							
	Attachments	Im	age - 1					

Approval and authorization

Requestor/holder	Approver	Reviewer
Name: Raj Kumar Pativada	Name: NA	Name: NA
Phone: +91916094443	Phone: NA	Phone: NA
Requested On: 22-Nov-2024 05:50:24 PM	Approved On: NA	Reviewed On: NA