Doc No: MHCPL-EHS-PTW-09



## Permit To Work Report - Lifting Work (Permit UID - APS/AKR/AMBUJ/LW/0006)

Type of permit	Lifting Work					
Name of project/ site	Akrida					
Contractor company	AMBUJA CEMENT					
Name of client/ contractor	ABhinav S					
Work location						
Scope of work						
Work permit start date	8/22/2024 12:00:00 AM					
Work permit start time	11/13/2024 7:14:00 PM					
Work permit close date	8/22/2024 12:00:00 AM					
Work permit close time	11/13/2024 11:00:00 PM					
No. of workers	NA					
Tools/ equipments to be used						
Description of work						
Reference permit no.						
Location	NA					
Hazards	Crane Collapse □	Falling	Objects 🗆	Load Fail 🗆		Sling Failure □
	Overloading	High W	ind 🗖	Bad Weather 🗖		Hit by Load □
	Other Hazards :					
Precautions						
taken	Other Precautions :		Swing Area Barricading □		Follow SWL of Crane / Sling	
	Adequate Illuminiation		HIRA Undertake	n 🗖	Good H	ousekeeping 🗖
	Good Sling Angle □		Proper Supervis	ion 🗆	Safe Ac	ccess / Egress
	Awareness on expected emergencies ? □					

Toolbox talks	{ToolboxTalks}						
PPEs	Safety Helmet □	Safety Helmet ☐ Safety Shoes ☐ Hand Gloves ☐					
	Goggles □	Other PPE's :					
Safety considerations	Cranes/Hydra crane should not be used for side pulls. Only freely suspended load may be side pulled.						
	Is Certified rigger medically fit & sufficiently trained?						
	Make sure operator must avoid carrying loads over people.						
	Make sure hook have safety latch. The load is well balanced. Avoid tip loading, and loading on hook latch.						
	Special permission to be obtained from site in charge after considering following guidelines for travelling with suspended load.(Try to avoid By travelling with suspended load)						
	Use tested lifting tool-tackles of appropriate capacity.(sling / synthetic belt / D-shackle / tailing hook etc.)						
	Ensure that the deployed operator is well trained, licensed, experienced, and competent to operate the particular Hydra crane to which they are assigned on the particular job involved.						
	Do not use slings, eye bolts, shackles, or hooks that have been cut, welded, or brazed.						
	Initially lift the load only a few inches to test the rigging and balance Loads should be well secured.						
	While any employee is touching the load or hook, there shall be no Hoisting, lowering, or traveling.						
	when the load or hook approaches near or over persons, the warning signal shall be sounded.						
	Make sure to complete the entire lifting operations on during the day light only. If at all to be carried during night hours ensure to provide sufficient lighting.						
	Make sure that no worker or any person is allowed to stay at lifting area. Avoid unauthorized entry. (Like Cars, Two wheelers, & pedestrians)						

## Approval and authorization

Requestor/holder	Issuer	Approver	Reviewer
Name: ABhinav S	Name: Dhruv Pahadia	Name: NA	Name: NA
Phone: NA	Phone: NA	Phone: NA	Phone: NA
Requested On: 22-Aug-2024 07:15:30	Issued On: 22-Aug-2024 07:41:52	Approved On:	Reviewed On:
PM	PM	NA	NA